

MAVERICK

AHL0053

APPLICATIONS: EDC, OUTDOOR, HIKING, TREKKING, WORK SAFETY, INDUSTRY, ENERGY

ANSI FL1 STANDARD

✱ 595 lm

◀ 170 m

POWER SUPPLY	Li-Po 3,7V 800 mAh / 3 x AAA			
CHARGING TIME	2 h 30 min			
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE	PEAK BEAM INTENSITY
HIGH (Li-Po)	530 lm	2 h 30 min	170 m	7236 cd
MEDIUM (Li-Po)	240 lm	5 h 50 min	115 m	3386 cd
LOW (Li-Po)	30 lm	22 h 30 min	40 m	400 cd
FLASHING 2 Hz (Li-Po)	-	1 h 30 min	-	-
HIGH (3 x AAA)	595 lm	2 h 30 min	170 m	7295 cd
MEDIUM (3 x AAA)	275 lm	6 h	110 m	3145 cd
LOW (3 x AAA)	35 lm	35 h	40 m	415 cd
FLASHING 2 Hz (3 x AAA)	-	1 h 30 min	-	-
DIMENSIONS	62 x 45 x 46 mm			
WEIGHT	88 g (without battery), 109 g (with battery)			
THE SET INCLUDES	Li-Po battery, USB-C cord, headband			



ADDITIONAL ACCESORIES:

AHL0053B	Li-Po 3,7V 800 mAh rechargeable battery (USB-C)
AHL0051M	Helmet mount with double-sided hook and loop
T-AHL0053-MOUNT	Helmet mount with 3M tape



IP64 RATING



2 m IMPACT RESISTANCE



USB-C CHARGING



DUAL SOURCE SYSTEM



FOCUS



MOTION SENSOR



ADVANCED DIMMING SYSTEM

Maverick headlamp delivers 595 lumens of light and offers four modes, allowing you to adjust brightness for various needs. It features an adjustable focus and a motion sensor for automatic activation. The beam distance reaches up to 170 meters, with 2 hours and 30 minutes running in High mode. The headlamp can be powered by a USB-C rechargeable battery or three AAA batteries. An IP64 rating protects it against dust and water splashes, and its 2-meter impact resistance to drops enhances durability. This versatile tool is ideal for outdoor activities, DIY projects, and everyday use.

PRODUCT MEETS THE FOLLOWING STANDARDS:

MACTRONIC[®]
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY



PATENTED
DESIGN



ECO FRIENDLY
PACKAGING

SCAN ME

