

CAMO II

AHL015

APPLICATIONS: OUTDOOR, CAMPING, EDC, HUNTING, INDUSTRY, UTILITIES

ANSI FL1 STANDARD

✦ 490 lm

◀ 150 m

POWER SUPPLY	3 x AA			
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE	PEAK BEAM INTENSITY
FRONT WHITE LIGHT				
HIGH	490 lm	4 h	150 m	5380 cd
MEDIUM	200 lm	17 h	90 m	2170 cd
LOW	30 lm	64 h	34 m	310 cd
8 Hz FLASHING	-	28 h	-	-
REAR RED LIGHT				
CONSTANT	-	130 h	-	-
FLASHING	-	365 h	-	-
DIMENSIONS	73 x 54 x 40 mm / 82 x 31 x 52 mm			
WEIGHT	145 g (without batteries), 215 g (with batteries)			
THE SET INCLUDES	3 x AA batteries, headband			



Camo II is a rugged headlamp designed to meet the demands of users requiring reliable lighting in challenging terrains. It offers an adjustable light beam (focus function) with a maximum light output of 490 lumens, allowing precise control of the beam width and intensity according to the user's needs. Camo II operates in three working modes and is powered by three AA batteries. In energy-saving mode, it provides up to 64 hours of operation. Red signal LEDs on the battery pack enhance visibility during nighttime activities. With resistance to moisture, mud, and dust (IP64) and impact resistance to drops from up to 2 meters, Camo II is ideal for hunting, bushcraft, and trekking.

PRODUCT MEETS THE FOLLOWING STANDARDS:

MACTRONIC®
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY

PATENTED
DESIGN

ECO FRIENDLY
PACKAGING

